

TPRH1207P TYPE


●FEATURE

1. Dual winding inductors that can be used as a single inductor, SEPIC, Flyback, or other coupled inductor/transformer applications (1:1 turns ratio)
2. Windings can be connected in series or parallel, offering a wide range of inductance and current ratings
3. same as EATON DRQ127 series

●Applications


1. Body electronics
2. Advanced driver assistance systems
3. Infotainment and cluster electronics

●Shape and Dimension



A=12.0±0.30m/m ; B=12.0±0.30m/m ; C=8.50m/m MAX

●Schematics and Land Patterns(mm)



●Specification

Part Number	Leads connected in parallel				Leads connected in series			
	L(uH) ±20%	DCR(Ω) MAX.	Isat (A)	Irms (A)	L(uH) ±30%	DCR(Ω) Max	Isat (A)	Irms (A)
TPRH1207P-4R7M	4.7	0.019	14.9	7.4	18.8	0.076	7.70	3.6
TPRH1207P-5R6M	5.6	0.023	13.4	7.2	22.4	0.092	6.60	3.5
TPRH1207P-6R8M	6.8	0.024	13.1	6.9	27.2	0.096	6.40	3.4
TPRH1207P-8R2M	8.2	0.025	10.8	6.6	32.8	0.100	5.60	3.3
TPRH1207P-100M	10	0.029	10.5	6.2	40.0	0.116	5.40	3.2
TPRH1207P-120M	12	0.031	9.6	6.0	48.0	0.124	4.80	2.9
TPRH1207P-150M	15	0.036	9.1	5.8	60.0	0.144	4.30	2.7
TPRH1207P-180M	18	0.040	8.0	5.5	72.0	0.158	3.90	2.5
TPRH1207P-220M	22	0.048	6.8	5.2	88	0.19	3.50	2.2
TPRH1207P-270M	27	0.060	6.5	4.7	108	0.24	3.40	2.0
TPRH1207P-330M	33	0.075	5.6	4.2	132	0.30	3.10	1.7

Part Number	Leads connected in parallel				Leads connected in series			
	L(uH) ±20%	DCR(Ω) Max	Isat (A)	Irms (A)	L(uH) ±30%	DCR(Ω) Max	Isat (A)	Irms (A)
TPRH1207P-390M	39	0.080	5.5	3.6	156	0.32	2.80	1.6
TPRH1207P-470M	47	0.090	5.2	3.0	188	0.36	2.60	1.5
TPRH1207P-560M	56	0.095	4.5	2.8	224	0.38	2.40	1.4
TPRH1207P-680M	68	0.105	4.1	2.6	272	0.42	2.10	1.3
TPRH1207P-820M	82	0.140	3.8	2.3	328	0.56	1.90	1.2
TPRH1207P-101M	100	0.150	3.4	2.0	400	0.60	1.70	1.1
TPRH1207P-121M	120	0.205	3.2	1.9	480	0.82	1.60	1.0
TPRH1207P-151M	150	0.230	2.8	1.8	600	0.92	1.40	0.89
TPRH1207P-181M	180	0.255	2.5	1.7	720	1.02	1.30	0.84
TPRH1207P-221M	220	0.345	2.3	1.6	880	1.38	1.10	0.75
TPRH1207P-271M	270	0.450	2.1	1.5	1080	1.80	1.00	0.71
TPRH1207P-331M	330	0.510	1.9	1.3	1320	2.04	0.92	0.62
TPRH1207P-391M	390	0.560	1.7	1.1	1560	2.24	0.84	0.53
TPRH1207P-471M	470	0.765	1.6	0.87	1880	3.06	0.80	0.43
TPRH1207P-561M	560	0.845	1.5	0.83	2240	3.38	0.73	0.40
TPRH1207P-681M	680	1.145	1.3	0.76	2720	4.58	0.63	0.36
TPRH1207P-821M	820	1.275	1.2	0.69	3280	5.10	0.58	0.33
TPRH1207P-102M	1000	1.415	1.1	0.60	4000	5.66	0.56	0.30

Note1. Measurement frequency of Inductance value : at 100KHz, 0.25V

Note2. Measurement ambient temperature of L, DCR and IDC : at 25°C

Note3. Isat: DC current at which the inductance drops 30%(typ.) from its value without current

Note4. Irms: Average current for 40°C temperature rise from 25°C ambient


Note5. Packaging: Taping ; Quantity: 350pcs/reel

● Order Code(Part Number)


1. TYPE NAME : TPRH1207P
2. INDUCTANCE VALUE : 100(10uH)
3. INDUCTANCE TOLERANCE : M(±20%)

GENERAL CHARACTERISTICS

1. Operating temperature range: -40 TO + 125°C(Includes temperature when the coil is heated)
2. External appearance: On visual inspection, the coil has no external defects.
3. Terminal strength: After soldering. Between copper plate and terminals of coil. Push in two directions of X.Y withstanding at below conditions.
Terminal should not peel off. (refer to figure at right) 5. 0N 60 sec.
4. Insulating resistance: Over 100MΩ at 100V D.C. between coil and core.
5. Dielectric strength: No dielectric breakdown at 100V D.C. for 1 minute between coil and core.
6. Temperature characteristics: Inductance coefficient $(0\sim 2,000)\times 10^{-6}/^{\circ}\text{C}$ (-25~+80°C degree Celsius), inductance deviation within $\pm 5.0\%$, after 96 hours.
7. Humidity characteristics(Moisture Resistance): Inductance deviation within $\pm 5\%$, after 96 hours in 90~95% relative humidity at $40 \pm 2^{\circ}\text{C}$ and 1 hour drying under normal condition.
8. Vibration resistance: Inductance deviation within $\pm 5\%$, after vibration for 1 hour. In each of three orientations at sweep vibration (10~55~10 Hz) with 1.5mm P-P amplitudes.
9. Shock resistance: Inductance deviation within $\pm 5\%$, after being dropped once with 981m/s² (100G) shock attitude upon a rubber block method shock testing machine, in three different orientations.
10. Resistance to Soldering Heat: 260°C, 10 seconds(See attached recommend reflow)
11. Storage condition: Temperature Range: 0°C ~ 35°C ; -40°C ~ 125°C (after PCB) , Humidity Range: 50% ~ 70% RH
12. Use components within 12 months. If 12 months or more have elapsed, check solderability before use.
13. Reflow profile recommend:



Lead-free heat endurance test



Lead-free the recommended reflow condition

