

F4P4532EL TYPE


●FEATURE

1. For automobile signal line

●Applications

1. CAN-BUS

●Shape and Dimension and Schematics and Land Patterns(mm)



●Specification

Dimension in m/m

PART NO.	Common Mode Inductance (uH) (+50%/-30%)	Common Mode Impedance(Ω) at 10MHz	Rated Current (mA)	Rated Voltage Withstand Voltage (Vdc)	Insulation Resistance (M ohm)	DC Resistance (max.) (ohm)
F4P4532EL-110	11uH at 100KHz	300Ω Min. 600Ω typ.	250	50 125	10 min	0.6
F4P4532EL-220	22uH at 100KHz	500Ω Min. 1200Ω typ.	200	50 125	10 min	1.0
F4P4532EL-510	51uH at 100KHz	1000Ω Min. 2800Ω typ.	200	50 125	10 min	1.0
F4P4532EL-101	100uH at 100KHz	2000Ω Min. 5800Ω typ.	150	50 125	10 min	2.0


Note1. Measurement ambient temperature of electrical : at 20°C

Note2. Test equipment: HP4291A


Note3. Packaging: Taping ; Quantity: 500 Pieces/reel

GENERAL CHARACTERISTICS


- Operating temperature range: -40 TO + 125°C(Includes temperature when the coil is heated)
- External appearance: On visual inspection, the coil has no external defects.
- Terminal strength: After soldering. Between copper plate and terminals of coil. Push in two directions of X.Y withstanding at below conditions.
Terminal should not peel off. (refer to figure at right) 0.5kg Min –F4P4532EL.
- Insulating resistance: Over 100MΩ at 100V D.C. between coil and core.
- Dielectric strength: No dielectric breakdown at 100V D.C. for 1 minute between coil and core.
- Temperature characteristics: Inductance coefficient $(0\sim 2,000)\times 10^{-6}/^{\circ}\text{C}$ (-25~+80°C) , inductance deviation within±5.0%, after 96 hours.
- Humidity characteristics(Moisture Resistance): Inductance deviation within ±5%, after 96 hours in 90~95% relative humidity at $40 \pm 2^{\circ}\text{C}$ and 1 hour drying under normal condition.
- Vibration resistance: Inductance deviation within ±5%, after vibration for 1 hour. In each of three orientations at sweep vibration (10~55~10 Hz) with 1.5mm P-P amplitudes.
- Shock resistance: Inductance deviation within ±5%, after being dropped once with 981m/s² (100G) shock attitude upon a rubber block method shock testing machine, in three different orientations.
- Resistance to Soldering Heat: 260°C, 10 seconds(See attached recommend reflow)
- Storage environment: Storage condition: Temperature Range: 10°C ~ 35°C (Generally: 21°C ~ 31°C) , Humidity Range: 50% ~ 80% RH (Generally: 65% ~ 75%) ; Transportation condition: Temperature Range: -35°C ~ 85°C , Humidity Range: 50% ~ 95% RH
- Use components within 12 months. If 12 months or more have elapsed, check solderability before use.
- Reflow profile recommend:



Lead-free heat endurance test




Lead-free the recommended reflow condition




● F4P 4532EL (Impedance VS Frequency)


F4P4532EL-110




F4P4532EL-220




F4P4532EL-510



F4P4532EL-101



● Test circuit




COMMON MODE




NORMAL MODE

●F4P 4532EL (Eye Digram Graphic)


F4P4532EL-110



F4P4532EL-220



F4P4532EL-510



F4P4532EL-101

