

## SB TYPE

### ●FEATURE


1. Cost effective EMI filtering

### ●Applications

1. Filtering of power input pins of oscillators or logic devices using high speed clocks
2. Preventing oscillations in high frequency amplifiers

### ●Shape and Dimension

### ●Schematics




SB302540: A=4.00±0.30 m/m ; B= 3.00±0.15 m/m ; C=2.55±0.10 m/m ; E=1.30 m/m

SB302585: A=8.50±0.30 m/m ; B= 3.00±0.15 m/m ; C=2.55±0.10 m/m ; E=2.00 m/m

### ●Specification

Part Number	Z(Ω)@25MHz	Z(Ω)@100MHz	DCR(ΩMax)	IDC(A)(Max)
SB302540	25	38	0.6m	10
SB302585	50	76	0.9m	10

### ●Impedance




Note1. Frequency range: 1MHz to 300MHz

Note2. Measurement ambient temperature of L, DCR and IDC : at 25°C


Note3. Packaging: Taping ; Quantity: SB302540:500 Piece/reel ; SB302585: 500 Piece/reel

## GENERAL CHARACTERISTICS

- Operating temperature range: -40 TO + 105°C (Includes temperature when the coil is heated)
- External appearance: On visual inspection, the coil has no external defects.
- Terminal strength: After soldering. Between copper plate and terminals of coil. Push in two directions of X.Ywithstanding at below conditions.  
Terminal should not peel off. (refer to figure at right) 5. 0N 60 sec.
- Insulating resistance: Over 100MΩ at 100V D.C. between coil and core.
- Dielectric strength: No dielectric breakdown at 100V D.C. for 1 minute between coil and core.
- Temperature characteristics: Inductance coefficient (0~2,000)x10-6/°C (-25~+80°C).
- Humidity characteristics(Moisture Resistance): Inductance deviation within ±5%, after 96 hours in 90~95% relative humidity at 40 ±2°C and 1 hour drying under normal condition.
- Vibration resistance: Inductance deviation within ±5%, after vibration for 1 hour. In each of three orientations at sweep vibration (10~55~10 Hz) with 1.5mm P-P amplitudes.
- Shock resistance: Inductance deviation within ±5%, after being dropped once with 981m/s2 (100G) shock attitude upon a rubber block method shock testing machine, in three different orientations.
- Resistance to Soldering Heat: 260°C, 10 seconds(See attached recommend reflow)
- Storage environment: Storage condition: Temperature Range: 10°C ~ 35°C (Generally: 21°C ~ 31°C) , Humidity Range: 50% ~ 80% RH (Generally: 65% ~ 75%) ; Transportation condition: Temperature Range: -35°C ~ 85°C , Humidity Range: 50% ~ 95% RH
- Use components within 6 months. If 6 months or more have elapsed, check soldarability before use.
- Reflow profile recommend:



Lead-free heat endurance test



Lead-free the recommended reflow condition

